

## VISU-HP Series

### Double Sided Hanging Poster

The ultra-thin and ultra-light double-sided hanging poster, with two screens back to back in a metal casing of only 22mm thick and weighing less than 20kg, can be used in a variety of applications.

The screens are Full HD, support 24/7/365 continuous operation, have an expected lifetime of over 60.000 hours, a 178° wide viewing angle, resist exposure to high temperatures

The side facing inwards has a brightness of 450nits while the side facing outwards boasts 800nits. The content, different for both sides, is remotely updated via the integrated Android player.

The double-sided hanging posters are available in 43", 49" and 55" screen size and either in white or black finish.



## VISU-HP Series

### Double Sided Hanging Poster

#### Main Specification

<b>Display</b>		
Panel	43"	
Display Area (mm)	943 x 536cm	
Aspect Ratio	16:9	
Resolution	1920x1080	
Brightness	(A side)450cd/m <sup>2</sup> ; (B side)800cd/m <sup>2</sup>	
View Angle(CR>10)	178°	
Display Color	16.7M	
Backlit Life	60000h	
Respond Time	6.5ms	
<b>System Configuration</b>		
Operating System	Android 5.1	
CPU	Quad-Core cortex A17, 1.8G, RK3288	
GPU	Mali-T764	
Memory	2GB(Optional4GB)	
Storage	8GB	
<b>External Ports</b>		
Video/Audio	HDMI	
Network Ports	Ethernet	
Storage Extension	SD Card, (Maximum 32GB)	
Other Ports	USB 2.0 *2, HDMI IN*1, RJ45*1, VGA IN*1	
<b>Multimedia</b>		
Media File Formats	Video: RMVB, MPEG1/2/4, AVI, DIVX, XDIV, WMV9, H.264, VC-1, MOV, MKV, MP4, TS, M2T, VOB	
	Audio: MP3, WMA, WAV, EAAC+, MP2 dec, Vorbis (Ogg), AC3, FLAC(Lossless Audio), APE(Lossless Audio), BSAC ;	
	Image: BMP/PNG/GIF/JPEG(4088*4088) ;	
	Text: txt	
Display Mode	Full Screen	
Content Publish	WiFi, LAN, USB	
<b>Machine Parameter</b>		
Product Size (mm)	1178*635*23mm	
Carton Size (mm)	1238*685*81mm	
Mounting Method	Ceiling Hanged	
Language	Chinese, English, Others, TTF Vector font supported. Display without distortion.	
Product Weight	Net-Weight: 18kg	Gross-Weight: 22kg
Power Consumption	220W	
Power Supply	AC 100-230	
Working Environment	0-40°C	
Working Humidity	0-90%	
Storage Environment	-20-60°C	
Storage Humidity	0-95%	
Accessory	Certification, Power Cable, Remote	